Total No. of Questions—8]

[Total No. of Printed Pages-3

Seat	
No.	

[4657]-587

S.E. (Information Technology) (Second Semester) EXAMINATION, 2014 PROCESSOR ARCHITECTURE AND INTERFACING (2012 PATTERN)

Time : Two Hours

N.B. :- (i) Answer Q. Nos. 1 or 2, Q. Nos. 3 or 4, Q. Nos. 5 or 6, Q. Nos. 7 or 8.

- (ii) Neat diagrams must be drawn wherever necessary.
- (*iii*) Figures to the right indicate full marks.
- (iv) Assume suitable data if necessary.
- 1. (a) State instruction example for the following addressing modes of 80386 showing physical address generation : [6]
 - (i) Direct
 - (ii) Based indexed
 - (iii) Scale indexed with displacement.
 - (b) Draw the general segment descriptor format. Explain how G (granularity) bit affects the LIMIT field. [6]

Or

- **2.** (a) Compare and contrast : [6]
 - (i) .COM and .EXE
 - (ii) NEAR procedure and FAR procedure.
 - (b) Explain with suitable control signals, the timing diagram of a non-pipelined write cycle of the 80386 processor. [6]

P.T.O.

Maximum Marks : 50

. . .

- (a) Draw and explain Programmer's model of 80386 in protected mode operation.
 - (b) What is privileged instruction ? Explain two examples of it. [6]

Or

- 4. (a) State and explain the difference between all operating modes of 80386. [6]
 (b) Explain IDT of 80386 in detail with diagram and
 - (b) Explain IDT of 80386 in detail with diagram and format. [6]
- 5. (a) Draw and explain architecture of 8051 Microcontroller. [7]
 - (b) Explain any three addressing modes in 8051 microcontroller with example. [6]

Or

- 6. (a) Explain the following instructions in 8051: [6]
 - (*i*) ORL A, #36
 - (ii) MUL AB
 - (iii) SWAP A.
 - (b) Explain program status word (PSW) in 8051 microcontroller. [7]

 $\mathbf{2}$

- (a) State and explain SFR's required for serial communication in 8051 microcontroller. [7]
 - (b) Draw and explain TCON and TMOD SFR's of 8051 microcontroller. [6]

Or

8.	<i>(a)</i>	List an	d explain	n an	two	operatin	ıg	modes	of	Timer	of
		8051.									[7]
	(<i>b</i>)	Explain	different	types	of i	interrupt	in	8051.			[6]