



AISSMS INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.: **AISSMS IOIT / 2025-26 / 904**

Date : **01/08/2025**

Tender Notice

Sealed/Online tenders are invited from reputed and experienced suppliers, manufacturers, or authorized distributors for the **supply, installation, and commissioning of equipment, tools, and machines** for setting up an **AICTE IDEA Lab** at our institute. The laboratory is to be developed as per the AICTE guidelines for promoting innovation, design thinking, and prototyping skills among students and faculty. The detailed specifications of the required items are enclosed with this document.

Sr. No	Equipments	Specifications	Preferred brands if any	Qty
1.	Single Nozzle 3D printer	Printing Technology: Fused Filament Fabrication (FFF) or Fused Deposition Modeling (FDM). Printable Area: The minimum printable area should be at least 310 x 310 x 310 mm or above Printer Design: Core XY or Cartesian. Temperature Range: Hot end: Up to 300°C or above Heat bed: Up to 120°C. or above. Nozzle: Compatible with All polymers, 0.4, 0.6 and 0.8mm Steel Sheet: Provided with satin or smooth PEI surface. Filament Diameter: 1.75mm (supports PLA, PETG, ASA, ABS, etc.). Extruder: Gearbox with 1/10 ratio, Speed : 550 MM/Sec or above Stepper Drivers for smooth motion. or equivalent Stepper Motors: Choose between 1.8° or precise 0.9° X, Y stepper motors. LCD Screen: 3.5" graphic 65k color screen or larger. Connectivity: USB drive, LAN, or internet. Supported Materials: PLA, PETG, ASA, ABS, PP, PC, flexible filaments, and more. Wi-Fi Module: Built-in (network connectivity not required for setup or operation).	Product with at least three years product warranty	1



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI

Honorary Secretary

DR. PRADEEP B. MANE

Principal

Ref. No.:

Date :

		Compatibility: Windows, macOS, Linux. Printer Dimensions: The maximum physical dimensions of the system 700 X 700 X 700 or above. Fully enclosed Machine.		
2.	PCB Milling Machine	Cutttable Materials: Modeling Wax, Chemical Wood, Foam, Acrylic, Poly Acetate, ABS, PCB, Copper glad, etc Table Size: 225 (X) × 150 (Y) mm or more Drive System: Stepping Motor (X, Y, Z Axis) Operating Speed: 800 mm/min Software Resolution: 0.01 mm/step Position accuracy : 0.01 to 0.02 mm Max Travel Speed (mm/sec)-58 (2.28 ") Drilling (mm)-0.2 -3.175 (8-125 mil) Maximum Drilling Cycles/ Min-50 Spindle Motor: DC Motor Type 380 or More Spindle Speed: Adjustable 20,000 and above rpm or more Tool Chuck Type: Collet Interface: USB or cable Control Commands: RML-1, NC code Power Supply: DC 24V, 2.5A (via AC 100-240V, 50/60Hz adapter) Power Consumption: Approx. 50 W or more	Product with at least three years product warranty	1
3.	CO2 Laser Cutting Machine	Working Area: Min 600 x 900 mm or above Laser Type: CO2 DC Glass Laser Tube/RF Metal Laser Tube Laser Power: 80/100W Wave Length: Upto 10.6 Micrometer Cutting Speed: 30000 mm/min or more Engraving Speed: 64000 mm/min or more XY Axis: LM Guide Rail or equivalent Cooling: Air/ Water Cooling Supply Voltage: 230V/415 V Accessories: CO2 Focus Lens: 1 No. Mirror 25mm: 3 Nos. Acetone: 1-litre Acrylic sheet: 2 Nos	Product with at least three years product warranty	1



AISSMS INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI

Honorary Secretary

DR. PRADEEP B. MANE

Principal

Ref. No.:

Date :

4.	Vinyl Printer	Dimensions: 50 cm x 15 cm x 15 cm or above Weight: 15.4 lbs or less Max cut size using machine mat: 11.5 inch x 23.5 inch or more Cut speed: up to 14.1 ips	Product with at least Two years Warranty	1
5.	3D Scanner	Technology: Stereo camera structured light with focusable cameras or equivalent CPU: Quad-core 64-bit SoC, 1.5GHz with integrated GPU RAM: 4 GB Projector: DLP MEMS mirror or equivalent Camera Sensor: Sony 13 MP or better Scan Speed: 4 seconds or more Working Distance : Effective Working Distance: 160mm-1400mm Scan Speed : 980,000points/s, up to 14FPS Align Modes : Feature Alignment, Hybrid Alignment, Texture Alignment, Global Markers Safety : Eye-safe Texture Scan : Yes Interface : USB2.0 or above Outdoor Scanning : Yes Output Formats : OBJ; STL; PLY; P3; 3MF Scanning Environment: Indoor and outdoor (shaded) Texture / Color Scanning: Yes Minimum Capturable Feature Size: 0.2 mm or less Scanner Weight: 500 grams or less Scanner Dimensions: upto 240 × 60 × 60 mm Compatible OS: Any OS supporting a modern web browser	Product with at least three years product warranty	1
6.	Lathe Machine cum milling	Centre Width: Up to 400 mm or better Height of Centers: Up to 88 mm Maximum Workpiece Diameter: Up to 100 mm Machine Base: Cross-ribbed	Product with at least three years	1



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		surface, high-quality cast iron with ground prismatic guide, capable of fitting milling/drilling attachment Spindle: Supported with adjustable taper roller bearings Spindle Receiver: MK3 or compatible Spindle Drill Hole: Up to 22 mm or better Spindle Concentricity: Up to 5 microns or better Chuck: 3-jaw chuck as per DIN 6386, centrally clamped, 100 mm diameter or better Run Out (without Chuck): Up to 10 microns Sleeve Receiver: MK2, retractable sleeve with scale Spindle Speed Range: Between 50 to 2500 rpm Speed Stages: 6-8 Motor Rating: 550W or better, induction motor, single phase 230V Traverse Cross: Up to 70 mm or better Traverse Longitudinal: Up to 300 mm or better Weight (Complete): Up to 55 kg or more Additional Accessories: Splash guard and chip collecting tray: 1 No. Cutter set with tungsten inserts: 2 Nos. Milling Attachment: 1nos Tungsten disposable tips ten-piece set: 1 No. Sample workpieces (Nylon Rod, Aluminium Rod) Desktop: 1 No.	product warranty	
7.	CNC Router	Working Area: Min 1300 x 2500 mm Z Axis Working Area: 200 or above Resolution: $\pm 0.03/300$ mm or more CNC Spindle: 3KW or more Lathe Structure : Welding Steel Structure or equivalent XYZ Structure: Rack Pinion , Ball Screw Linear Rails Max Spindle Speed : Min 18000RPM Table: T-Slot/Vacuum Bed/Water Bed Repeatability: ± 0.03 Working Mode: Stepper Motor/Servo Motor Dust	Product with at least three years product warranty	1



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		Collector : To be included by Vendor Voltage: AC 220V/415V, 50/60 Hz, 3 Phase		
8.	Belt and Disc Sanding Machine	Motor: 230V 50Hz Power: 380W S2 30min No-load Speed: 1450rpm or more Belt Size: 100x914mm or less Disc Size: 150mm or better Table Titing Range: 0°- 45° Belt Titing Range: 0°-90° Table Size: upto 190x125mm	Branded Company Product with at least three years product warranty	1
9.	Scroll Saw	Power input: 50 Watt Thickness of Cut: 50 mm (2 inch) Throat: 406 mm (16 inch) Length of Stroke: 18 mm (11/16 inch) Strokes Per Minute: 400-1,600 SPM Overall Length: 600 mm (23-5/8 inch)	Product with at least three years product warranty	1
10.	Wood Turning Lathe	Motor: 230V~50Hz, 550W, S2:15min or above Max. Disc Diameter: min 75 mm Max. Cutting Length: 450 mm or more Spindle Speed: 5 speeds such as 1600 / 2600 / 3200 RPM etc Material: Cast Iron Bed Height: 0.2 m Cable Length: 0.850 m	Product with at least three years product warranty	1
11.	Bench Top Drill Machine	Continuous rating input: Max. 250 W Capacity: Steel: Min 13 mm (1/2") Wood: Min 24 mm (15/16") No Load Speed (RPM): 570, 890, 1,300, 1,900, 2,670(50 Hz), 690, 1,070, 1,560, 2,280, 3,200(60 Hz) Net weight: Max. 20 kg (44.1 lbs.) Power supply cord: 1.75 m (5.7 ft) Additional Accessories: Bench Vise: 1 No., Drill Bit Set 10 Pcs: 1 No	Product with at least Three to Five years Warranty	1
12.	Portable Welding Machine	Welding Current (at 40°C, 10 min cycle): 120A @ 100%, 150A @ 60%, 200A @ 35% Supply Voltage: 240V +10%, -15%, 1 Phase, 50/60 Hz Open Circuit Voltage:	Product with at least Three to	1



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		55V DC $\pm 5V$ Welding Current Range: 15–200 Amps DC Insulation Class: F Type Ingress Protection: IP21 Dimensions (L×W×H) with Handle: upto 320×120×195 mm Weight (Approx.): 4.3 kg or less	Five years Warranty	
13.	Computerized Sewing Machine	Motor: 120 W Max Sewing Speed: 860 SPM Power: 220 - 240 V Automation Grade: Automatic Max Stitch Length: 4mm Thread Type: Computerized Weight: 7.6 kg Number of Stitches: 120 Size/Dimension: 50.8 cm x 29.464 cm x 40.64 cm Maximum Stitch Width: 7 mm Number of Buttonhole Styles: 7 LCD Screen Display: Yes Bed Type Free Arm/Flatbed convertible Bobbin Type Drop & Sew Bobbin System	Product with at least three years product warranty	1
14.	Filament Dehydrator	Operating Temperature Range: Min 45°C–70°C Drying Time Setting: 0–48 hours or higher Hot-Air Heating: upto 360° circulation Moving Speed: 300 mm/s or more Power Rating: 160 W Shipping Weight: 2.5 kg	Product with at least three years product warranty	1
15.	Reflow Oven	No. of Waves: 7 or higher Heating Type: Infrared IC Heater Max. PCB Width: 300×320 mm or more Power Supply: AC 220V / 50Hz Peak Power: 1500W Cycle Time: 1–8 min or less Temperature Range: 0°C–280°C Overall Dimensions: min 350×450 mm Machine Weight: upto 25 kg	Product with at least three years product warranty	1
16.	Digital multimeter	Display Count: Up to 4000 DC Voltage Range: Up to 1000 V AC Voltage Range: Up to 1000 V DC Voltage Accuracy: $\pm 0.5\%$ or ± 3 digits, whichever is higher AC Voltage Accuracy: Within $\pm 1\% + 3$	Product with at least three years product	5



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		digits DC Current Measurement: Up to 10 A AC Current Measurement: Maximum 10 A DC Current Accuracy: $\pm 1.5\%$ + 3 digits (approximate) AC Current Accuracy: $\pm 1.5\%$ + 3 digits (typical) Resistance Measurement: Up to 40 M Ω Resistance Accuracy: Estimated at $\pm 1.5\%$ + 3 digits Capacitance Measurement: Up to 1000 μ F Capacitance Accuracy: $\pm 5\%$ or ± 5 digits Operating Temperature Range: From 0°C up to approximately 40°C Storage Temperature Range: Between -30°C and 60°C Overall Dimensions (H×W×L): Approximately 183×91×49.5 mm Unit Weight: Around 455 grams Safety Compliance: As per IEC 61010-1 & IEC 61010-2-030 standards, suitable for CAT III 600V and CAT II 1000V environments with Pollution Degree 2 classification	warranty	
17.	MSO 100 MHz	Bandwidth: Up to 100 MHz Analog Channels: 4 or more Real-Time Sampling Rate: Maximum 1 GSa/s per channel Memory Depth: 10 Mpts per channel Waveform Update Rate: Approximately 120,000 wfms/s Vertical Resolution: 8 bits Vertical Scale: Ranging from 1 mV/div to 10 V/div Horizontal Scale: Spanning 1 ns/div to 100 s/div Spectrum Analyzer Frequency Range: DC to 500 MHz FFT Points: Up to 1M points for enhanced frequency domain resolution Waveform Math Functions: Includes addition, subtraction, multiplication, division, minimum, maximum, root, square, absolute, inverse, derivative, integral, and low-pass filter Trigger	Product with at least three years product warranty	1



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra

Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		Types: Edge, Pulse Width, Video, Pulse Runt, Rise & Fall (slope), Alternate, Timeout, Event-Delay, Time-Delay, and Bus Arbitrary Waveform Generator (AWG): Dual-channel, 25 MHz, supporting various waveforms such as sine, square, pulse, ramp, DC, noise, sinc, Gaussian, Lorentz, exponential rise/fall, haversine, and cardiac AWG Sample Rate: 200 MSa/s AWG Vertical Resolution: 14 bits Display: 8-inch WVGA TFT LCD (800 × 480 pixels) Data Logging Capability: Up to 1000 hours Segmented Memory: Supports up to 29,000 segments for efficient waveform storage and retrieval Connectivity: USB 2.0 (host and device), Ethernet (RJ45), and Go-NoGo BNC Dimensions (W × H × D): 380× 200× 125 mm or above Weight: 2 Kgs or above Safety Compliance: Conforms to IEC 61010-1 and IEC 61010-2-030 standards, suitable for CAT III 600V and CAT II 1000V environments with Pollution Degree 2 classification		
18.	Digital oscilloscope	Number of Channels: Up to 2 independent analog inputs Memory Record Length: Up to 10 Mpts for extended waveform capture Bandwidth Limiting: Selectable 20 MHz bandwidth filter Sampling Rate: Maximum of 1 GSa/s real-time equivalent per channel Rise Time: ≤ 3.5 ns depending on probe and settings Display: 7" TFT color LCD with 800×480 resolution Time Base Range: From 5 ns/div to 100 s/div, user-adjustable Vertical Resolution: 8-bit digital resolution Trigger Modes:	Product with at least three years product warranty	1



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		Automatic, Normal, and Signal-dependent triggering Maximum Input Voltage: 300 Vrms (within safety limits) Input Sensitivity: Within the range of 1 mV/div to 10 V/div Input Coupling Options: Selectable among AC, DC, and Ground Trigger Coupling Modes: Configurable as AC, DC, High-pass, or Low-pass Physical Dimensions: Approximately 350 × 200 × 120 mm or above Unit Weight: 2.5 kg or above Input Impedance: Nominal 1 MΩ // 16 pF Measurement Capabilities: Equipped for automatic parameter extraction, background noise filtering, and AUTOSET configuration for display scaling (time base/gain) Protocol Decoding Support: Capable of analyzing I2C, SPI, UART, CAN, and LIN communication protocols Standard Accessories: Includes mains power cable, user manual (digital format), and one GTL-16E probe per input channel		
19.	Power supply	Output Configuration: 4-channel design with independent electrical isolation across all outputs Channel Output Ranges: • CH1 & CH2: Adjustable output voltage from 0 to 32V with a current delivery capacity up to 3A • CH3: Variable range 0 to 5V supporting up to 1A • CH4: Output adjustable from 0 to 15V with a load current of up to 1A Constant Voltage Operating Mode Line Regulation: $\leq 0.01\% + 3 \text{ mV}$ (approximate value within rated voltage range) Load Regulation: $\leq 0.01\% + 3 \text{ mV}$ (across rated load variation) Ripple & Noise: $\leq 1 \text{ mVrms}$ across full bandwidth	Product with at least three years product warranty	1



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
– Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with “A+” Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		Constant Current Operating Mode Line Regulation: $\leq 0.2\% + 3 \text{ mA}$ Load Regulation: $\leq 0.2\% + 3 \text{ mA}$ Ripple Current: $\leq 3 \text{ mArms}$ (typical) Safety & Operational Features Output Control: Independent output ON/OFF switching functionality is required Voltage Resolution: Approximately 100 mV (*1) Current Resolution: Approximately 10 mA (*1) Display Parameters Display Units: Four separate displays required for individual channel status visualization Display Type: 4.3-inch LCD (color or monochrome as applicable) Functional Features Tracking Operation: Supported (required for synchronizing output behavior) Auto Series/Parallel: Supported (automatic internal reconfiguration required) Power Requirements Supply Input: 230V AC $\pm 10\%$, 50 Hz Mechanical Specifications Maximum Dimensions (W \times H \times D): Within 200 mm \times 100 mm \times 200 mm Maximum Weight: 10 kg or less		
20.	Function Generator	Output Function: The equipment shall provide output waveforms including sine, square, triangle, and TTL signals as required. Frequency Range: For sine and square waveforms: approximately 0.1 Hz up to 3 MHz. For triangle waveform: approximately 0.1 Hz up to 1 MHz. Frequency Resolution: Frequency resolution shall be maintained within a maximum of 0.1 Hz. Frequency Stability: The frequency stability shall be within ± 20 ppm (parts per million). Frequency Accuracy: The frequency accuracy shall	Product with at least three years product warranty	1



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		be maintained within ± 20 ppm. Frequency Aging: Frequency aging shall not exceed ± 5 ppm per annum. Amplitude Range: Output amplitude shall be up to 10 V peak-to-peak (V_{p-p}) into a 50Ω load. Amplitude Accuracy: Amplitude accuracy shall be within $\pm 20\%$ at maximum amplitude setting. Output Impedance: Nominal output impedance shall be 50Ω with a tolerance of $\pm 10\%$. Attenuator: A single-step attenuator of $-40 \text{ dB} \pm 1 \text{ dB}$ shall be provided. Display: A 6-digit LED display shall be incorporated for parameter indication. Output Control: Output shall be controlled via an ON/OFF selector switch. Power Source: The device shall operate on an AC supply of 240 V, 220 V, or 110 V $\pm 10\%$, with frequency 50/60 Hz. Ambient Operating Temperature: Normal operation shall be ensured within the ambient temperature range of 0°C to 40°C . Dimensions: Maximum dimensions shall not exceed 255 mm (W) \times 95 mm (H) \times 295 mm (D). Weight: Maximum device weight shall be within 2.5 kg.		
21.	Bench Top Multimeter	DC Voltage: Range: 500 mV to 1000 V across 5 ranges. Accuracy: $\pm(0.03\% \text{ rdg} + 4 \text{ digits})$. Input impedance: $10 \text{ M}\Omega$. AC Voltage (True RMS): Range: 500 mV to 1000 V across 5 ranges. Accuracy: $\pm(0.5\% - 5\% \text{ rdg} + \text{digits})$ depending on frequency and range. Input impedance: $10 \text{ M}\Omega$. DC Current: Range: 500 μA to 20 A across 6 ranges. Accuracy: $\pm(0.02\% - 0.3\% \text{ rdg} + 2 \text{ digits})$ depending on range. AC Current (True RMS): Range: 500 μA	Product with at least three years product warranty	1



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra

Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI

Honorary Secretary

DR. PRADEEP B. MANE

Principal

Ref. No.:

Date :

		to 20 A across 6 ranges. Accuracy: $\pm(0.5\% - 1\% \text{ rdg} + \text{digits})$ depending on frequency. Resistance: Range: 500 Ω to 20 M Ω across 6 ranges. Accuracy: $\pm(0.1\% - 0.3\% \text{ rdg} + \text{digits})$ depending on range. Diode Test: Max forward voltage 1.5 V, open voltage 2.8 V. Capacitance: Range: 5 nF to 50 μF . Accuracy: $\pm(2\% \text{ rdg} + 4 \text{ digits})$. Frequency: Input level varies by range; functions include Auto/Manual Range, Max, Min, dBm, Rel, Hold. Continuity Beep: Threshold $<5 \Omega$. Display: Dual 7-segment LED, 0.4" and 0.5". Power Source: AC 100/120/230 V $\pm 10\%$, 50/60 Hz. Dimensions & Weight: Approximately 251 \times 91 \times 291 mm; 2.6 kg.		
22.	Non-Contact Voltage Tester	Function: Non-contact AC voltage detection tester. Voltage Detection Range: Approximately 90 V to 1000 V AC. Detection Method: Capacitive, with visual and audible indication. Sensitivity: Adjustable sensitivity for different voltage ranges. Response Time: Instantaneous detection within standard operating conditions. Indicators: Bright LED indicators and audible beep for voltage presence. Operating Environment: Suitable for use in ambient temperatures from 0 $^{\circ}\text{C}$ to 40 $^{\circ}\text{C}$. Power Source: Powered by standard batteries (typically 2 \times AAA or equivalent). Safety Standards: Complies with IEC/EN 61010-1 CAT III 1000 V safety standards. Dimensions: Compact, handheld design suitable for field use (approx. 150 mm \times 30 mm \times 25 mm). Weight: Lightweight,	Product with at least three years product warranty	5



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		approximately 150 g for ease of portability.		
23.	LCR Meter	Display: Approximately 2.8" TFT touch LCD screen. Resolution: 25,000 or above counts resolution on both primary and secondary displays. Basic Accuracy: Within $\pm 0.2\%$ under standard conditions. Test Frequencies: Six or eight selectable frequencies depending on model variant. Measurement Combinations: Up to 15 different measurement combinations available. Test Level: Selectable AC test levels approximately 0.3 V, 0.7 V, and 1 V rms; DC test level selectable at ± 1 V. Measurement Speed: Selectable measurement speeds of approximately 10 measurements per second (fast) and 2.5 measurements per second (slow). Auto LCR Mode: Automatic identification and measurement of component types within supported ranges. Data Hold: Feature available to hold measured data on display. Interface: USB virtual COM port provided for remote communication capabilities. Software: Datalogging software available for data capture and analysis.	Product with at least three years product warranty	1
24.	Soldering Station	Power Rating: Approximately 60 W maximum output power. Temperature Range: Adjustable from approximately 200 °C up to 480 °C. Temperature Stability: Within ± 2 °C under normal operating conditions. Heating Element: Ceramic heating element for rapid heat-up and efficient temperature maintenance.	Product with at least three years product warranty	3



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra

Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI

Honorary Secretary

DR. PRADEEP B. MANE

Principal

Ref. No.:

Date :

		Display: Digital or analog temperature display (depending on variant) for precise temperature control. Temperature Control: Adjustable via knob or digital interface with fine resolution. Power Supply: AC 220 V $\pm 10\%$, 50/60 Hz. Safety Features: Thermal cutoff and overload protection within required standards. Dimensions: Compact design with 100 mm \times 100 mm \times 90 mm (W \times H \times D) or above Weight: Approximately 1.5 kg for ease of portability and bench use.		
25.	Digital Microscope	Specification: Magnification: 1600X Light source: 8 LED lights Resolution: 1920 \times 1080, 640*480 Pixel: 30W Focal length: 3-40mm manual adjustment Support Android 4.2 or above/widows/Mac system	Product with at least three years product warranty	1
26.	Soldering Rework Station	Soldering Iron Power: Up to approximately 60 W output power with temperature adjustable within approximately 200 $^{\circ}$ C to 480 $^{\circ}$ C range. Heating Element: Needle bit with MCH heater providing rapid heat-up and stable temperature control within ± 2 $^{\circ}$ C. Hot Air Blower Power: Up to approximately 500 W output power with temperature adjustable within approximately 200 $^{\circ}$ C to 450 $^{\circ}$ C range, multiple nozzles included. Hot Air Features: Auto-pause function on placement in cradle, airflow adjustable within operational limits. DC Power Supply: Provides output voltage approximately 15 V up to 2 A maximum current plus 5 V USB output for auxiliary power. Control: Microcontroller-based	Product with at least three years product warranty	1



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra

Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI

Honorary Secretary

DR. PRADEEP B. MANE

Principal

Ref. No.:

Date :

		system with LED indicators for temperature and mode selection. Safety: ESD-safe design compliant with applicable standards. Build: Metallic body with powder coating, approximate dimensions 280 mm × 180 mm × 140 mm (W × H × D). Weight: Approximately 3.5 kg. Power Source: AC 220 V ±10%, 50/60 Hz. Accessories: Includes soldering iron with needle bit, hot air blower with 3 nozzles, iron stand with sponge, hot air cradle, patch cord, and power cord. Operating Temperature: Suitable for ambient temperature approximately 0 °C to 40 °C		
27.	Hand Drill Machine	Rated Input Power: Approximately 500 W or above maximum power consumption. Bit Holder: Standard 1/2"-20 UNF thread type. No-Load Speed (1st Gear): Adjustable from 0 up to approximately 3,000 rpm. Power Output: Approximately 300 W continuous output power. Weight: Approximately 1.7 kg total device weight. Impact Rate at No-Load Speed: Variable from 0 up to approximately 48,000 bpm. Rated Torque: Approximately 1.4 Nm maximum torque output. Drill Spindle Connecting Thread: Standard 1/2"-20 UNF thread. Chuck Capacity (Min/Max): Approximately 1.5 mm minimum to 13 mm maximum.	Product with at least three years product warranty	2
28.	Cordless drill	Torque (soft/hard/max.): Min 21/50/- Nm No-load speed (1st gear / 2nd gear): Min 0 - 500 / 0 - 1,900 rpm Weight incl. battery: 1.3 kg or less Max. impact rate: 27,000 bpm Battery type:	Product with at least three years product	2



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		Lithium-Ion or equivalent Chuck capacity, min./max.: 1.5 / 13 mm Weight excl. battery: 0.99 kg Torque settings: 20+2 or better	warranty	
29.	Jig Saw	Rated Input Power: Approximately 500 W maximum power consumption. Voltage, Electrical: Nominal 230 V AC supply. Saw Stroke Length: Approximately 20 mm stroke length. Stroke Rate at No Load: Adjustable within approximately 800 to 3,100 spm (strokes per minute). Weight: Approximately 2.08 kg total weight. Bevel Angle: Adjustable within approximately -45° to 45° range.	Product with at least three years product warranty	1
30.	Miter Saw	Rated Input Power: Approximately 1,750 W maximum power consumption. Saw Blade Diameter: Approximately 254 mm nominal diameter. Mitre Setting: Adjustable up to approximately 47° left and 52° right. Bevel Setting: Adjustable up to approximately 45° left and 0° right. Saw Blade Bore Diameter: Approximately 25.4 mm standard bore. Cutting Capacity at 0°: Approximately 90 mm × 130 mm maximum cross-section. Cutting Capacity at 45° Mitre: Approximately 90 mm × 91 mm maximum cross-section. Cutting Capacity at 45° Bevel: Approximately 60 mm × 130 mm maximum cross-section. Tool Dimensions (W×L×H): Approximately 477 mm × 559 mm × 567 mm. No-Load Speed: Fixed at approximately 5,000 rpm. Weight: Approximately 11.1 kg.	Product with at least three years product warranty	1
31.	Hot air gun	Rated Input Power: Approximately 1,800 W maximum power consumption.	Product with at	2



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		Voltage, Electrical: Nominal 230 V AC supply. Weight: Approximately 0.75 kg. Working Temperature Range: Adjustable within approximately 60 °C to 550 °C. Heat-Up Time: Approximately 1 second to reach target temperature. Airflow: Adjustable within approximately 350 to 550 liters per minute. Airflow Control: Three selectable airflow settings.	least three years product warranty	
32.	Table saw	Rated input power: Max 1800 W Incline setting: 45° L / 0° R Table size: Up to 555 x 555 mm Saw blade diameter: 254 mm Cutting height 90°: 80 mm Cutting height 45°: 55 mm Saw blade bore diameter: 30 mm Weight: 24.4 kg or less Max. cutting capacity on the right: 545 mm No-load speed: 4300 rpm Cutting height 90°: 80 mm Cutting height 45°: 55 mm	Product with at least three years product warranty	1
33.	Bench grinder	Grinding wheel diameter: min 150 mm Rated input power: 350 W or more Grinding wheel widths: 20 mm or more No-load speed: upto 3,000 rpm Grinding wheel bore: 20 mm/2cm Grit 24, 60 or more Weight: 10 kg or less	Product with at least three years product warranty	1
34.	Angle Grinder	Rated Input Power: Approximately 670 W maximum power consumption. No-Load Speed: Approximately 11,000 rpm. Disc Diameter: Approximately 100 mm nominal diameter. Grinding Spindle Thread: Standard M10 thread. Weight: Approximately 1.5 kg. Switch: Lockable switch for operational safety.	Product with at least three years product warranty	1
35.	Straight Grinder	Rated Input Power: Max 300 W power	Product	1



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		consumption. No-Load Speed: Up to 28,000 rpm. Voltage, Electrical: Nominal 230 V AC supply. Spindle Collar Diameter: Approximately 41 mm. Weight: Around 1.4 kg. Maximum Grinding Tool Diameter: Up to 25 mm. Maximum Collet Diameter: Up to 8 mm. Switch: Lockable switch for enhanced safety.	with at least three years product warranty	
36.	Circular Saw	Rated Input Power: Approximately 1,400 W maximum consumption. Saw Blade Diameter: Nominal 184 mm diameter. Saw Blade Bore Diameter: About 20 mm standard bore size. Guide Rail Compatibility: Not compatible with guide rails. No-Load Speed: Typically 5,200 rpm. Weight: Around 4.1 kg	Product with at least three years product warranty	1
37.	Blower	Rated Input Power: Max 650 W power consumption. Weight: Approximately 1.7 kg. Voltage, Electrical: Nominal 230 V AC supply. Sound Pressure Level: Around 103 dB(A). Sound Power Level: Approximately 95 dB(A). Uncertainty (K): Within ± 3 dB	Product with at least three years product warranty	1
38.	Cordless Screw Driver	Battery Capacity: Around 1.5 Ah nominal capacity. Torque (Soft/Hard/Max): Approximately 14 Nm / 30 Nm / Maximum not specified. No-Load Speed (1st Gear / 2nd Gear): Ranges from 0 up to 400 rpm and 0 up to 1,500 rpm respectively. Battery Type: Rechargeable Lithium-Ion battery. Chuck Capacity (Min/Max): From approximately 0.8 mm up to 10 mm. Weight (Excluding Battery): About 0.8 kg. Torque Settings:	Product with at least three years product warranty	1



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		20 plus 1 adjustable settings.		
39.	Vacuum Cleaner	Rated Input Power: Approximately 1,100 W maximum power consumption. Weight: Around 6 kg total weight. Container Volume (Net): Approximately 10 liters capacity. Voltage, Electrical: Nominal 230 V AC supply. Container Volume (Gross): Approximately 15 liters total volume. Container Volume (Net, Water): About 8 liters capacity for water. Filter Surface Area: Around 2,300 cm ² effective filtration area. Airflow Rate (Turbine): Approximately 53 liters per second. Vacuum Pressure (Turbine): Up to 270 mbar vacuum pressure. Number of Wheels: Four wheels for mobility	Product with at least three years product warranty	1
40.	Random orbit sander	Rated Input Power: Up to 280 W maximum consumption. Sanding Pad Diameter: Nominal 125 mm diameter. Orbit Diameter: Approximately 2.6 mm orbital diameter. Weight: Around 1.4 kg. No-Load Speed: Adjustable within 7,500 to 12,000 rpm range. Orbital Stroke Rate: Between 15,000 and 24,000 orbits per minute (opm). Eccentricity: Approximately 1.3 mm.	Product with at least three years product warranty	1
41.	Planer	Rated Input Power: Not exceeding 710 W under nominal operating conditions. Planing Width: Approximately 82 mm effective width capacity. Planing Depth: Within the range of up to 2.6 mm maximum depth per pass. Weight: Circa 2.8 kg total unit mass. Adjustable Rebating Depth: Maximum adjustable depth of approximately 9 mm. No-Load	Product with at least three years product warranty	1



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		Speed: Operating speed typically around 18,000 rpm.		
42.	Cordless Vacuum Cleaner with Starter kit	Battery Voltage: Rated at approximately 18.0 V nominal voltage. Weight Excluding Battery: Around 1.3 kg without battery attached. Container Volume: Approximately 0.7 liters net capacity. Filter Surface Area: Roughly 55 cm ² filtration surface. Maximum Airflow Rate (Turbine): Up to 10 liters per second. Maximum Vacuum Pressure (Turbine): Not exceeding 60 mbar under standard conditions. Operating Time (18 V Battery): Typically 7 minutes per Ah of battery capacity.	Product with at least three years product warranty	1
43.	Rotary Tool Kit	Rated Power Input: Approximately 175 W within nominal voltage range. Voltage: Operates within 220 to 240 V AC supply. Weight: Around 0.66 kg total mass. Length: Approximately 24 cm overall length. Width: About 4.1 cm nominal width. Depth: Roughly 4.3 cm depth dimension. No-Load Speed: Variable speed ranging from 5,000 up to 35,000 rpm. Battery Technology: Not applicable (n.a.). Speed Setting: Fully variable speed control as required. Accessory Quick Change System: Equipped with multi chuck for rapid accessory interchange. Vibration Level: Approximately 18 m/s ² measured vibration	Product with at least three years product warranty	2
44.	Rubber Grip Hacksaw	Depth of Throat: Approximately 98 mm (3.85 inches) nominal depth. Blade Length: Around 254 mm (10 inches) standard length.	Very Good Quality	2



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		be maintained within ± 20 ppm. Frequency Aging: Frequency aging shall not exceed ± 5 ppm per annum. Amplitude Range: Output amplitude shall be up to 10 V peak-to-peak (V_{p-p}) into a 50Ω load. Amplitude Accuracy: Amplitude accuracy shall be within $\pm 20\%$ at maximum amplitude setting. Output Impedance: Nominal output impedance shall be 50Ω with a tolerance of $\pm 10\%$. Attenuator: A single-step attenuator of $-40 \text{ dB} \pm 1 \text{ dB}$ shall be provided. Display: A 6-digit LED display shall be incorporated for parameter indication. Output Control: Output shall be controlled via an ON/OFF selector switch. Power Source: The device shall operate on an AC supply of 240 V, 220 V, or 110 V $\pm 10\%$, with frequency 50/60 Hz. Ambient Operating Temperature: Normal operation shall be ensured within the ambient temperature range of 0°C to 40°C . Dimensions: Maximum dimensions shall not exceed 255 mm (W) \times 95 mm (H) \times 295 mm (D). Weight: Maximum device weight shall be within 2.5 kg.		
21.	Bench Top Multimeter	DC Voltage: Range: 500 mV to 1000 V across 5 ranges. Accuracy: $\pm(0.03\% \text{ rdg} + 4 \text{ digits})$. Input impedance: $10 \text{ M}\Omega$. AC Voltage (True RMS): Range: 500 mV to 1000 V across 5 ranges. Accuracy: $\pm(0.5\% - 5\% \text{ rdg} + \text{digits})$ depending on frequency and range. Input impedance: $10 \text{ M}\Omega$. DC Current: Range: 500 μA to 20 A across 6 ranges. Accuracy: $\pm(0.02\% - 0.3\% \text{ rdg} + 2 \text{ digits})$ depending on range. AC Current (True RMS): Range: 500 μA	Product with at least three years product warranty	1



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes.

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		to 20 A across 6 ranges. Accuracy: $\pm(0.5\%-1\%$ rdg + digits) depending on frequency. Resistance: Range: 500 Ω to 20 M Ω across 6 ranges. Accuracy: $\pm(0.1\%-0.3\%$ rdg + digits) depending on range. Diode Test: Max forward voltage 1.5 V, open voltage 2.8 V. Capacitance: Range: 5 nF to 50 μ F. Accuracy: $\pm(2\%$ rdg + 4 digits). Frequency: Input level varies by range; functions include Auto/Manual Range, Max, Min, dBm, Rel, Hold. Continuity Beep: Threshold <5 Ω . Display: Dual 7-segment LED, 0.4" and 0.5". Power Source: AC 100/120/230 V $\pm 10\%$, 50/60 Hz. Dimensions & Weight: Approximately 251 \times 91 \times 291 mm; 2.6 kg.		
22.	Non-Contact Voltage Tester	Function: Non-contact AC voltage detection tester. Voltage Detection Range: Approximately 90 V to 1000 V AC. Detection Method: Capacitive, with visual and audible indication. Sensitivity: Adjustable sensitivity for different voltage ranges. Response Time: Instantaneous detection within standard operating conditions. Indicators: Bright LED indicators and audible beep for voltage presence. Operating Environment: Suitable for use in ambient temperatures from 0 $^{\circ}$ C to 40 $^{\circ}$ C. Power Source: Powered by standard batteries (typically 2 \times AAA or equivalent). Safety Standards: Complies with IEC/EN 61010-1 CAT III 1000 V safety standards. Dimensions: Compact, handheld design suitable for field use (approx. 150 mm \times 30 mm \times 25 mm). Weight: Lightweight,	Product with at least three years product warranty	5



AISSMS INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		approximately 150 g for ease of portability.		
23.	LCR Meter	Display: Approximately 2.8" TFT touch LCD screen. Resolution: 25,000 or above counts resolution on both primary and secondary displays. Basic Accuracy: Within $\pm 0.2\%$ under standard conditions. Test Frequencies: Six or eight selectable frequencies depending on model variant. Measurement Combinations: Up to 15 different measurement combinations available. Test Level: Selectable AC test levels approximately 0.3 V, 0.7 V, and 1 V rms; DC test level selectable at ± 1 V. Measurement Speed: Selectable measurement speeds of approximately 10 measurements per second (fast) and 2.5 measurements per second (slow). Auto LCR Mode: Automatic identification and measurement of component types within supported ranges. Data Hold: Feature available to hold measured data on display. Interface: USB virtual COM port provided for remote communication capabilities. Software: Datalogging software available for data capture and analysis.	Product with at least three years product warranty	1
24.	Soldering Station	Power Rating: Approximately 60 W maximum output power. Temperature Range: Adjustable from approximately 200 °C up to 480 °C. Temperature Stability: Within ± 2 °C under normal operating conditions. Heating Element: Ceramic heating element for rapid heat-up and efficient temperature maintenance.	Product with at least three years product warranty	3



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		Display: Digital or analog temperature display (depending on variant) for precise temperature control. Temperature Control: Adjustable via knob or digital interface with fine resolution. Power Supply: AC 220 V $\pm 10\%$, 50/60 Hz. Safety Features: Thermal cutoff and overload protection within required standards. Dimensions: Compact design with 100 mm \times 100 mm \times 90 mm (W \times H \times D) or above Weight: Approximately 1.5 kg for ease of portability and bench use.		
25.	Digital Microscope	Specification: Magnification: 1600X Light source: 8 LED lights Resolution: 1920 \times 1080, 640 \times 480 Pixel: 30W Focal length: 3-40mm manual adjustment Support Android 4.2 or above/widows/Mac system	Product with at least three years product warranty	1
26.	Soldering Rework Station	Soldering Iron Power: Up to approximately 60 W output power with temperature adjustable within approximately 200 $^{\circ}$ C to 480 $^{\circ}$ C range. Heating Element: Needle bit with MCH heater providing rapid heat-up and stable temperature control within ± 2 $^{\circ}$ C. Hot Air Blower Power: Up to approximately 500 W output power with temperature adjustable within approximately 200 $^{\circ}$ C to 450 $^{\circ}$ C range, multiple nozzles included. Hot Air Features: Auto-pause function on placement in cradle, airflow adjustable within operational limits. DC Power Supply: Provides output voltage approximately 15 V up to 2 A maximum current plus 5 V USB output for auxiliary power. Control: Microcontroller-based	Product with at least three years product warranty	1



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		system with LED indicators for temperature and mode selection. Safety: ESD-safe design compliant with applicable standards. Build: Metallic body with powder coating, approximate dimensions 280 mm × 180 mm × 140 mm (W × H × D). Weight: Approximately 3.5 kg. Power Source: AC 220 V ±10%, 50/60 Hz. Accessories: Includes soldering iron with needle bit, hot air blower with 3 nozzles, iron stand with sponge, hot air cradle, patch cord, and power cord. Operating Temperature: Suitable for ambient temperature approximately 0 °C to 40 °C		
27.	Hand Drill Machine	Rated Input Power: Approximately 500 W or above maximum power consumption. Bit Holder: Standard 1/2"-20 UNF thread type. No-Load Speed (1st Gear): Adjustable from 0 up to approximately 3,000 rpm. Power Output: Approximately 300 W continuous output power. Weight: Approximately 1.7 kg total device weight. Impact Rate at No-Load Speed: Variable from 0 up to approximately 48,000 bpm. Rated Torque: Approximately 1.4 Nm maximum torque output. Drill Spindle Connecting Thread: Standard 1/2"-20 UNF thread. Chuck Capacity (Min/Max): Approximately 1.5 mm minimum to 13 mm maximum.	Product with at least three years product warranty	2
28.	Cordless drill	Torque (soft/hard/max.): Min 21/50/- Nm No-load speed (1st gear / 2nd gear): Min 0 – 500 / 0 – 1,900 rpm Weight incl. battery: 1.3 kg or less Max. impact rate: 27,000 bpm Battery type:	Product with at least three years product	2



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		Lithium-Ion or equivalent Chuck capacity, min./max.: 1.5 / 13 mm Weight excl. battery: 0.99 kg Torque settings: 20+2 or better	warranty	
29.	Jig Saw	Rated Input Power: Approximately 500 W maximum power consumption. Voltage, Electrical: Nominal 230 V AC supply. Saw Stroke Length: Approximately 20 mm stroke length. Stroke Rate at No Load: Adjustable within approximately 800 to 3,100 spm (strokes per minute). Weight: Approximately 2.08 kg total weight. Bevel Angle: Adjustable within approximately -45° to 45° range.	Product with at least three years product warranty	1
30.	Miter Saw	Rated Input Power: Approximately 1,750 W maximum power consumption. Saw Blade Diameter: Approximately 254 mm nominal diameter. Mitre Setting: Adjustable up to approximately 47° left and 52° right. Bevel Setting: Adjustable up to approximately 45° left and 0° right. Saw Blade Bore Diameter: Approximately 25.4 mm standard bore. Cutting Capacity at 0°: Approximately 90 mm × 130 mm maximum cross-section. Cutting Capacity at 45° Mitre: Approximately 90 mm × 91 mm maximum cross-section. Cutting Capacity at 45° Bevel: Approximately 60 mm × 130 mm maximum cross-section. Tool Dimensions (W×L×H): Approximately 477 mm × 559 mm × 567 mm. No-Load Speed: Fixed at approximately 5,000 rpm. Weight: Approximately 11.1 kg.	Product with at least three years product warranty	1
31.	Hot air gun	Rated Input Power: Approximately 1,800 W maximum power consumption.	Product with at	2



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		Voltage, Electrical: Nominal 230 V AC supply. Weight: Approximately 0.75 kg. Working Temperature Range: Adjustable within approximately 60 °C to 550 °C. Heat-Up Time: Approximately 1 second to reach target temperature. Airflow: Adjustable within approximately 350 to 550 liters per minute. Airflow Control: Three selectable airflow settings.	least three years product warranty	
32.	Table saw	Rated input power: Max 1800 W Incline setting: 45 ° L / 0 ° R Table size: Up to 555 x 555 mm Saw blade diameter: 254 mm Cutting height 90°: 80 mm Cutting height 45°: 55 mm Saw blade bore diameter: 30 mm Weight 24.4 kg or less Max. cutting capacity on the right: 545 mm No-load speed: 4300 rpm Cutting height 90°: 80 mm Cutting height 45°: 55 mm	Product with at least three years product warranty	1
33.	Bench grinder	Grinding wheel diameter: min 150 mm Rated input power: 350 W or more Grinding wheel widths: 20 mm or more No-load speed: upto 3,000 rpm Grinding wheel bore: 20 mm/2cm Grit 24, 60 or more Weight: 10 kg or less	Product with at least three years product warranty	1
34.	Angle Grinder	Rated Input Power: Approximately 670 W maximum power consumption. No-Load Speed: Approximately 11,000 rpm. Disc Diameter: Approximately 100 mm nominal diameter. Grinding Spindle Thread: Standard M10 thread. Weight: Approximately 1.5 kg. Switch: Lockable switch for operational safety.	Product with at least three years product warranty	1
35.	Straight Grinder	Rated Input Power: Max 300 W power	Product	1



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		consumption. No-Load Speed: Up to 28,000 rpm. Voltage, Electrical: Nominal 230 V AC supply. Spindle Collar Diameter: Approximately 41 mm. Weight: Around 1.4 kg. Maximum Grinding Tool Diameter: Up to 25 mm. Maximum Collet Diameter: Up to 8 mm. Switch: Lockable switch for enhanced safety.	with at least three years product warranty	
36.	Circular Saw	Rated Input Power: Approximately 1,400 W maximum consumption. Saw Blade Diameter: Nominal 184 mm diameter. Saw Blade Bore Diameter: About 20 mm standard bore size. Guide Rail Compatibility: Not compatible with guide rails. No-Load Speed: Typically 5,200 rpm. Weight: Around 4.1 kg	Product with at least three years product warranty	1
37.	Blower	Rated Input Power: Max 650 W power consumption. Weight: Approximately 1.7 kg. Voltage, Electrical: Nominal 230 V AC supply. Sound Pressure Level: Around 103 dB(A). Sound Power Level: Approximately 95 dB(A). Uncertainty (K): Within ± 3 dB	Product with at least three years product warranty	1
38.	Cordless Screw Driver	Battery Capacity: Around 1.5 Ah nominal capacity. Torque (Soft/Hard/Max): Approximately 14 Nm / 30 Nm / Maximum not specified. No-Load Speed (1st Gear / 2nd Gear): Ranges from 0 up to 400 rpm and 0 up to 1,500 rpm respectively. Battery Type: Rechargeable Lithium-Ion battery. Chuck Capacity (Min/Max): From approximately 0.8 mm up to 10 mm. Weight (Excluding Battery): About 0.8 kg. Torque Settings:	Product with at least three years product warranty	1



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		20 plus 1 adjustable settings.		
39.	Vacuum Cleaner	Rated Input Power: Approximately 1,100 W maximum power consumption. Weight: Around 6 kg total weight. Container Volume (Net): Approximately 10 liters capacity. Voltage, Electrical: Nominal 230 V AC supply. Container Volume (Gross): Approximately 15 liters total volume. Container Volume (Net, Water): About 8 liters capacity for water. Filter Surface Area: Around 2,300 cm ² effective filtration area. Airflow Rate (Turbine): Approximately 53 liters per second. Vacuum Pressure (Turbine): Up to 270 mbar vacuum pressure. Number of Wheels: Four wheels for mobility	Product with at least three years product warranty	1
40.	Random orbit sander	Rated Input Power: Up to 280 W maximum consumption. Sanding Pad Diameter: Nominal 125 mm diameter. Orbit Diameter: Approximately 2.6 mm orbital diameter. Weight: Around 1.4 kg. No-Load Speed: Adjustable within 7,500 to 12,000 rpm range. Orbital Stroke Rate: Between 15,000 and 24,000 orbits per minute (opm). Eccentricity: Approximately 1.3 mm.	Product with at least three years product warranty	1
41.	Planer	Rated Input Power: Not exceeding 710 W under nominal operating conditions. Planing Width: Approximately 82 mm effective width capacity. Planing Depth: Within the range of up to 2.6 mm maximum depth per pass. Weight: Circa 2.8 kg total unit mass. Adjustable Rebating Depth: Maximum adjustable depth of approximately 9 mm. No-Load	Product with at least three years product warranty	1



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		Speed: Operating speed typically around 18,000 rpm.		
42.	Cordless Vacuum Cleaner with Starter kit	Battery Voltage: Rated at approximately 18.0 V nominal voltage. Weight Excluding Battery: Around 1.3 kg without battery attached. Container Volume: Approximately 0.7 liters net capacity. Filter Surface Area: Roughly 55 cm ² filtration surface. Maximum Airflow Rate (Turbine): Up to 10 liters per second. Maximum Vacuum Pressure (Turbine): Not exceeding 60 mbar under standard conditions. Operating Time (18 V Battery): Typically 7 minutes per Ah of battery capacity.	Product with at least three years product warranty	1
43.	Rotary Tool Kit	Rated Power Input: Approximately 175 W within nominal voltage range. Voltage: Operates within 220 to 240 V AC supply. Weight: Around 0.66 kg total mass. Length: Approximately 24 cm overall length. Width: About 4.1 cm nominal width. Depth: Roughly 4.3 cm depth dimension. No-Load Speed: Variable speed ranging from 5,000 up to 35,000 rpm. Battery Technology: Not applicable (n.a.). Speed Setting: Fully variable speed control as required. Accessory Quick Change System: Equipped with multi chuck for rapid accessory interchange. Vibration Level: Approximately 18 m/s ² measured vibration	Product with at least three years product warranty	2
44.	Rubber Grip Hacksaw	Depth of Throat: Approximately 98 mm (3.85 inches) nominal depth. Blade Length: Around 254 mm (10 inches) standard length.	Very Good Quality	2



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

45.	Hacksaw Mini	Blade Length: Approximately 10 inches nominal length. Handle Material: Constructed from metal as standard. Overall Length: Around 11 inches total length.	Very Good Quality	2
46.	Claw Hammer Steel Shaft	Weight: Approximately 8 oz (220 grams) nominal weight. Dimensions: Around 27.8 cm × 12.4 cm × 3.6 cm (L × W × H) overall size	Very Good Quality	2
47.	Ball Pein Hammer	Weight: Approximately 110 grams nominal weight. Dimensions: Around 32.6 cm × 10 cm × 2 cm (L × W × H) overall measurements.	Very Good Quality	2
48.	Rubber mallet	Weight: Approximately 450 grams nominal weight. Dimensions: Around 33.6 cm × 9.6 cm × 6.2 cm (L × W × H) overall size.	Very Good Quality	2
49.	Ring spanner set 12Pcs	Weight: 3.08 Kg nominal weight. Quantity: 12 pcs per set. Size: 6 mm to 32 mm overall range.	Very Good Quality	1
50.	Open end spanner set 12Pcs	Weight: Approx 1.74Kg nom.wt. Qty: 12pcs/set. Size: 6mm-32mm overall dims.	Very Good Quality	1
51.	Combination Spanner set 8Pcs	Weight: Approx 649g nom.wt. Qty: 8pcs/set.	Very Good Quality	1
52.	Allen key set 10pcs	Hex Key Size: 1.5, 2, 2.5, 3, 4, 5, 5.5, 6, 8, 10mm; Qty: 10pcs/set	Very Good Quality	2
53.	Allen key set 12pcs	Ball Key Size: 1/16", 5/64", 3/32", 7/64", 1/8", 9/64", >5/32", 3/16", 7/32", 1/4", 5/16", 3/8" Qty: 12pcs/set	Very Good Quality	2
54.	Combination plier	Weight: Approx 422g nom.wt. Size: 8"/200mm nominal	Very Good Quality	2



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI

Honorary Secretary

DR. PRADEEP B. MANE

Principal

Ref. No.:

Date :

55.	Long nose plier	Weight: Approx 399g Size: 180mm/6" nominal	nom.wt.	Very Good Quality	2
56.	Circlip straight 5"	Weight: Approx 399g Size: 130mm/5" nominal	nom.wt.	Very Good Quality	2
57.	Circlip bent	"Weight: Approx 399g Size: 130mm/5"" nominal"	nom.wt.	Very Good Quality	2
58.	Diagonal Cutter	"Weight: Approx 239g Size: 180mm nominal"	nom.wt.	Very Good Quality	2
59.	Wire Stripper	Weight: Approx 281g Size: 130mm nominal	nom.wt.	Very Good Quality	2
60.	Adjustable spanner	Size: Upto 150 mm		Very Good Quality	2
61.	Pipe wrench	Size: Max 300 mm		Very Good Quality	2
62.	C – clamp	Size: Upto 75 mm		Very Good Quality	4
63.	C-clamp	Size: Upto 150 mm		Very Good Quality	4
64.	Snap- off Knife	Size: 18 mmm		Very Good Quality	2
65.	16pcs screw driver set	Pieces Per Set: 16 pcs		Very Good Quality	1
66.	6pcs precision screw driver set	Pieces Per Set: 16 pcs		Very Good Quality	2
67.	Max steel snip cutter	Length: 250 mm		Very	2



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

			Good Quality	
68.	PVC Pipe cutter	Length: 42 mm	Very Good Quality	2
69.	Hot Glue Gun	Power: 40 W	Very Good Quality	4
70.	Small file set	Length: 160 mm	Very Good Quality	2
71.	Big file set	Length: 200 mm	Very Good Quality	2
72.	Chisel set	Weight: 340 gm	Very Good Quality	2
73.	Punch set	Weight: 390 gm	Very Good Quality	2
74.	Bench wise	Base Type: Fixed Size:2-3½" nominal JawWidth:60mm	Very Good Quality	2
75.	Router Bit Starter Kit	Pieces Per Set: 15 pcs	Very Good Quality	1
76.	Drill bit set	WAF(mm):1,1.5,2,2.5,3,3.5,4,4.5,5,5.5, 6,6.5,7,7.5,8,8.5,9,9.5,10,10.5,11,11.5,12, 12.5,13 Wt:~1.3Kg nom.wt Sz(mm):205×115×55 overall	Very Good Quality	2
77.	Baby wise	Vice Type: Bench Size:2" nominal JawWidth:50mm	Very Good Quality	2
78.	Ratchet Set	Vice Type: Bench Sz:2" nominal; Jaw:50mm	Very Good Quality	2
79.	Pegboard		Very	5



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

			Good Quality	
80.	Digital Vernier Caliper	Product Type: Digital Calliper Meas.Range:0-150mm / 0-6" Resolution:0.01mm	Very Good Quality	2
81.	Micrometer	Resolution:0.001mm/0.00005" Meas.Range:0-25mm/0-1"	Very Good Quality	1
82.	Steel Rule 300mm	Product Type: Steel Rule ScaleSize:12"/300mm Material: Stainless Steel	Very Good Quality	5
83.	Steel Rule 600mm	Product Type: Steel Rule ScaleSize:24"/600mm Material: Stainless Steel	Very Good Quality	5
84.	Engineering Square	Size:150×80mm nominal Material: Carbon Steel	Very Good Quality	2
85.	Meter Tape 30m	Length: 30 m	Very Good Quality	1
86.	Measuring Tape 3M	Length: 3 m	Very Good Quality	3
87.	Measuring Tape 5M	Length: 5 m	Very Good Quality	3
88.	Spirit Level	Vials:3 Accuracy:0.5mm/m Length:300mm Product Type: Level	Very Good Quality	3
89.	Goggle	Goggle – Industrial Standard Make	Very Good Quality	5
90.	Apron	Apron - Standard Make	Very Good Quality	5
91.	Ear Muff	Earmuff – Industrial Standard Make	Very Good	5



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

			Quality	
92.	Mask	Mask – Industrial Standard Make	Very Good Quality	50
93.	Fire Extinguisher	Fire Extinguisher– Industrial Standard Make	Very Good Quality	6
94.	First Aid Kit	First Aid Kit – Industrial Standard Make	Very Good Quality	2
95.	Gloves Pair	Gloves – Industrial Standard Make	Very Good Quality	10
96.	Normal Oven	Oven Cap: 20L or more Type: Solo Door: Side Swing Child Lock: Yes Completion Beeper: Yes Power Levels: upto 5 Control: Membrane Type Cavity Mat: Anti-Bacterial Dims(mm):455×252×320 PowerOut:700W or less	Branded Company Product with at least three years product warranty	1
97.	Refrigerator	Capacity:183L or more AnnualEnergyConsumption:148kWh/Year or less RefrigeratorFreshFoodCapacity:165L or more Freezer Capacity: min 18L BottleCount:5 or more NoiseLevel:40dB or less Installation Type: Freestanding	Branded Company Product with at least three years product warranty	1
98.	Smart Board	Display Size: Approx 75Inch (190 cm) Up to Resolution: 4KUHDorHigher Brightness: Min 350 nits; Typ400nitsApprox Contrast Ratio: Typ 1200: 1Upto Response Time: Approx 8ms Viewing Angle: Approx178DegreesWide WorkingFrequency:1.5GHzNominal	Branded Company Product with at least three years product warranty	1



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		RAM:4GBOrMore InternalStorage:32GBMin OS: Android Based HDMI: 3Ports USB: 2Ports Sensing Type: Infrared Touch Frame Surface Protection: 4mm Toughened Glass Or Equivalent Infrared Touch Points: 20Approx Voltage:DC+5V±5%Range OPS: Optional		
99.	Projector	Projection Tech: RGB liquid crystal shutter projection (3LCD) Up to Connectivity: USB Type B: 1port (FirmwareUpdate/Copy OSD) Approx AnalogInput:D-Sub15pin:1port Digital Input: HDMI:1port Projection Lens: Type: No Optical Zoom/Focus (Manual)Nominal FocalLength:16.70mm Approx FNumber:1.44 Nominal Zoom:1.44-1.95 Ratio (Wide to Tele) ThrowRatioRange:1.00–1.35(Digital Zoom Approx	Branded Company Product with at least three years product warranty	1
100.	Printer	Functions: Print, Scan, Copy Printer Type: Laser Nominal Dims(mm):409×398.5×267 Approx Weight:9.7KgNominal PrintSpeed:Upto30ppm(A4Size) Approx Warranty:1YearOn-Site PrintResolution:600×600dpi, HQ1200 (2400×600dpi) Quality Approx 2Sided- Duplex-PaperType:Plain,Thin, RecycledApprox 2Sided-Duplex- PaperSize:A4 PaperHandling: Tray#1- PaperType:Plain,Thin,Recycled Tray#1- MaxCapacity:Upto250Sheets(80g/m ²)Ap prox PaperOutput:Upto100Sheets(80g/m ²)	Branded Company Product with at least three years product warranty	1



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

		FaceDownTray;OneSheetFaceUpTrayAp prox Copy- Colour /Mono: Yes/Yes Multiple Copies: Sorts/StacksUpto99PagesApprox Enlarge/Reduce:25%- 400%(In1%Steps)Approx CopyResolution:600×600dpi 2Sided- Duplex- CopyPaperType:Plain,Thin,Recycled 2Sided-Duplex-CopyPaperSize:A4 Scan- ResolutionInterpolated:Upto19200×1920 0dpi Approx Scan- ResolutionGlass:Upto600×2400dpiAppro x Connectivity:Hi-SpeedUSB2.0 DisplayType:16Chars×2Lines MemoryCapacity:32MBApprox PowerSource:220-240VAC50/60Hz PowerConsumption-Ready:Approx60W PowerConsumption-Sleep:Approx6.6W PowerConsumption-Off:Approx0.08W NoiseLevel:50dB(A)Approx		
101.	Desktop	CPU: INTEL CORE I7-12THGEN or Higher RAM:8GB+512GB SSD or more Conn: LAN+WIFI+BLUTOOTH+KEYMOUSE Display:20" DESKTOP MONITOR	Branded Company Product with at least three years product warranty	5
102.	3D printer Filament	Weight Kg: 1 Approx Melt Flow Index: 2 (190°C/2.16kg) Nominal FilamentLength:330mApprox Dim Accuracy: +/-0.1mmApprox Roundness Accuracy: +/-0.5mmApprox SpoolInnerDia:55mmNominal SpoolOuterDia:200mmApprox SpoolWeight:300gNominal SpoolWidth:65mmApprox	Very Good Quality	10



AISSMS INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

103.	Acrylic Sheet 3mm, 4ft x 4ft		Very Good Quality	20
104.	Acrylic Sheet 4mm, 4ft x 4ft		Very Good Quality	20
105.	Acrylic Sheet 5mm, 4ft x 4ft		Very Good Quality	20
106.	Foam Sheet 8mm, 4ft x 4ft		Very Good Quality	2
107.	Foam Sheet 10mm, 4ft x 4ft		Very Good Quality	1
108.	Foam Sheet 12mm, 4ft x 4ft		Very Good Quality	1
109.	Foam Sheet 15mm, 4ft x 4ft		Very Good Quality	1
110.	Ply Board 5mm, 2ft x 4ft		Very Good Quality	12
111.	Nylon Rod 10mm, 1m		Very Good Quality	5
112.	Nuts (3mm,4mm,5mm, 6mm,8mm,10mm, 12mm) Pack of 100		Very Good Quality	1
113.	Bolts (3mm,4mm,5mm, 6mm,8mm,10mm,12 mm) dia 1" Inch Pack of 100		Very Good Quality	1



AISSMS INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

114.	Screws (3mm,4mm,5mm) Pack of 100		Very Good Quality	1
115.	Washers (3mm,4mm,5mm, 6mm,8mm,10mm,12 mm) Pack of 100		Very Good Quality	1
116.	Studs (6mm,8mm) 1 Meter		Very Good Quality	2
117.	Nails (1",2",3",1.5",5") Pack of 100		Very Good Quality	1
118.	Fevicol 2Kg		Very Good Quality	1
119.	2 Way Tape		Very Good Quality	10
120.	PVC Pipe .75",10ft		Very Good Quality	10
121.	PVC Pipe 1",10ft		Very Good Quality	10
122.	PVC Pipe 1.5",10ft		Very Good Quality	10
123.	PVC Pipe 2.0",10ft		Very Good Quality	10
124.	Aluminium channels (L, C, Box, strip length 12ft)		Very Good Quality	2
125.	PCB Drill Bit 0.4mm		Very Good Quality	10



AISSMS INSTITUTE OF INFORMATION TECHNOLOGY (IOIT)



ADDING VALUE TO ENGINEERING

An Autonomous Institute Affiliated to Savitribai Phule Pune University
Approved by AICTE, New Delhi and Recognised by Govt. of Maharashtra
Accredited by NAAC with "A+" Grade | NBA - 5 UG Programmes

SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

DR. PRADEEP B. MANE
Principal

Ref. No.:

Date :

126.	PCB Drill Bit 0.8mm		Very Good Quality	10
127.	PCB Drill Bit 1mm		Very Good Quality	10
128.	Drill Bit 4mm		Very Good Quality	10
129.	Drill Bit 5mm		Very Good Quality	10
130.	Drill Bit 6mm		Very Good Quality	10
131.	Arduino UNO R3		Very Good Quality	5
132.	Arduino NANO		Very Good Quality	5
133.	Arduino Mega		Very Good Quality	3
134.	Raspberry Pi Model 4B, 4GB		Very Good Quality	3
135.	ESP8266 NodeMCU		Very Good Quality	2
136.	ESP32 Development Board		Very Good Quality	2
137.	Beaglebone blu		Very Good Quality	1
138.	Beaglebone Black		Very	1



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY

ADDING VALUE TO ENGINEERING

Approved by AICTE, New Delhi, Recognized by Govt. of Maharashtra,
Affiliated to Savitribai Phule Pune University (ID No. PU / PN / ENGG / 124 / 1998)

Accredited by NAAC with 'A' Grade



SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

Dr. PRADEEP B MANE
Principal

Ref. No.:

Date :

			Good Quality	
139.	Voltage Regulator Module		Very Good Quality	2
140.	Mini Micro submersible Water Pump		Very Good Quality	2
141.	Piezoelectric Plate		Very Good Quality	2
142.	8*8 LED Matrix Module		Very Good Quality	2
143.	Bluetooth		Very Good Quality	2
144.	7 Segment LED Display		Very Good Quality	2
145.	GSM/GPRS/GPS Module		Very Good Quality	2
146.	Laser Module		Very Good Quality	2
147.	LDR Module		Very Good Quality	2
148.	4*4 Matrix Keypad		Very Good Quality	2
149.	Joy Stick Module		Very Good Quality	2
150.	Active Buzzer (BIG)		Very Good	2



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY

ADDING VALUE TO ENGINEERING

Approved by AICTE, New Delhi, Recognized by Govt. of Maharashtra,
Affiliated to Savitribai Phule Pune University (ID No. PU / PN / ENGG / 124 / 1998)

Accredited by NAAC with 'A' Grade



SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

Dr. PRADEEP B MANE
Principal

Ref. No.:

Date :

			Quality	
151.	Active Buzzer (SMALL)		Very Good Quality	2
152.	Motor Driver		Very Good Quality	2
153.	Sound Playback Module		Very Good Quality	2
154.	BO Motors		Very Good Quality	10
155.	Vibrating Motor		Very Good Quality	10
156.	Capacitive Touch Switch		Very Good Quality	2
157.	IR Sensors (Obstacle Sensors)		Very Good Quality	2
158.	Triple Axis Magnetometer		Very Good Quality	2
159.	Humidity Sensor		Very Good Quality	2
160.	MQ-2		Very Good Quality	2
161.	MQ-3		Very Good Quality	2
162.	MQ-4		Very Good Quality	2



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY

ADDING VALUE TO ENGINEERING

Approved by AICTE, New Delhi, Recognized by Govt. of Maharashtra,
Affiliated to Savitribai Phule Pune University (ID No. PU / PN / ENGG / 124 / 1998)

Accredited by NAAC with 'A' Grade



SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

Dr. PRADEEP B MANE
Principal

Ref. No.:

Date :

163.	MQ-5		Very Good Quality	2
164.	MQ-7		Very Good Quality	2
165.	Ultrasonic Sensor Module		Very Good Quality	2
166.	Triple Axis accelerometer		Very Good Quality	2
167.	PIR Motion Detector Module		Very Good Quality	2
168.	Pulse Rate Heart Sensor		Very Good Quality	2
169.	Relay Module		Very Good Quality	2
170.	Soil Moisture Sensor		Very Good Quality	2
171.	Touch Sensor		Very Good Quality	2
172.	Rain Drop Sensor		Very Good Quality	2
173.	Flex Sensor		Very Good Quality	2
174.	Temperature Sensor		Very Good Quality	2
175.	Force Pressure		Very	2



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY

ADDING VALUE TO ENGINEERING

Approved by AICTE, New Delhi, Recognized by Govt. of Maharashtra,
Affiliated to Savitribai Phule Pune University (ID No. PU / PN / ENGG / 124 / 1998)

Accredited by NAAC with 'A' Grade



SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

Dr. PRADEEP B MANE
Principal

Ref. No.:

Date :

	Sensor		Good Quality	
176.	Colour Recognition Sensor		Very Good Quality	2
177.	Water Flow Sensor		Very Good Quality	2
178.	Sound Sensor		Very Good Quality	2
179.	IR Sensor Array for Line Following		Very Good Quality	2
180.	RFID Reader-Tags		Very Good Quality	2
181.	RF Modules Tx& Rx 315 MHz ASK		Very Good Quality	2
182.	Stepper motor with Driver Board		Very Good Quality	2
183.	Servo Motor 360 rotation		Very Good Quality	10
184.	Servo Motor 180 rotation		Very Good Quality	10
185.	Metal Gear Servo Motor (180° Rotation)		Very Good Quality	10
186.	Solder Wire 100gms		Very Good Quality	10
187.	Solder Flux		Very Good	10



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY

ADDING VALUE TO ENGINEERING

Approved by AICTE, New Delhi, Recognized by Govt. of Maharashtra,
Affiliated to Savitribai Phule Pune University (ID No. PU / PN / ENGG / 124 / 1998)

Accredited by NAAC with 'A' Grade



SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

Dr. PRADEEP B MANE
Principal

Ref. No.:

Date :

			Quality	
188.	830 Points Solderless Breadboard		Very Good Quality	5
189.	400 Points Solderless Breadboard		Very Good Quality	5
190.	Copper Clad Board single side		Very Good Quality	10
191.	Copper clad board double side		Very Good Quality	10
192.	Male to Male Breadboard Jumper		Very Good Quality	10
193.	Female to Female Breadboard Jumper		Very Good Quality	10
194.	Male to Female Breadboard Jumper		Very Good Quality	10

Terms and Conditions

The following Terms and Conditions apply to all bidders participating in the tender for the supply, installation, and commissioning of equipment, tools, and machines for the establishment of an AICTE IDEA Lab. All prospective vendors are required to read and comply with these terms in their entirety.

1. General Information

All equipment and materials must be delivered in the quantities and specifications as mentioned in the purchase order issued by the purchaser. The delivery location will be specified in the purchase order AISSMS Institute Of Information Technology, Kennedy road, Near RTO, Pune. The entire contract shall remain valid for a period of three (3) months from the date of award.



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY

ADDING VALUE TO ENGINEERING

Approved by AICTE, New Delhi, Recognized by Govt. of Maharashtra,
Affiliated to Savitribai Phule Pune University (ID No. PU / PN / ENGG / 124 / 1998)

Accredited by NAAC with 'A' Grade



SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

Dr. PRADEEP B MANE
Principal

Ref. No.:

Date :

Quotations submitted by bidders must remain valid for a minimum of 90 days from the final date of submission. Any quotation that does not meet this validity period will be considered non-compliant.

2. Bid Submission Guidelines

Bids may be submitted either via email (digitally signed) or in hard copy form, as specifically mentioned in the tender notice. All quotations must be printed on the bidder's official letterhead and duly signed by an authorized representative.

Each bid must be complete in all respects and must include the following mandatory documents:

- Detailed Profile of the Bidder, highlighting experience and key competencies.
- Copy of the Company/Firm Registration Certificate.
- Copy of valid GST Registration Certificate.
- Copy of submitted GST return (at least up to November 2024).
- Copy of valid PAN Card.
- Chartered Accountant's Certificate for turnover for FY 2021-22, 2022-23, and 2023-24.
- CA-certified and audited Balance Sheets and Financial Statements (Form 3CB/3CA) for the last three financial years.
- Copies of Work Completion or Experience Certificates of similar completed works.
- Valid Shop Establishment License or Factory License.
- Genuine Manufacturer Authorization Form (MAF), which will be subject to verification with the respective OEM.
- Bidder should provide an Escalation Matrix for service and after sales support.
- Valid EPF, ESIC, and Professional Tax Registration Certificates (where applicable).
- Income Tax Return Acknowledgements for FY 2021-22, 2022-23, and 2023-24.
- Declaration/Affidavit (on ₹500/- Stamp Paper) regarding no blacklisting from IITs/NITs/Govt. Offices/PSUs/Autonomous Bodies.



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY

ADDING VALUE TO ENGINEERING

Approved by AICTE, New Delhi, Recognized by Govt. of Maharashtra,
Affiliated to Savitribai Phule Pune University (ID No. PU / PN / ENGG / 124 / 1998)

Accredited by NAAC with 'A' Grade



SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

Dr. PRADEEP B MANE
Principal

Ref. No.:

Date :

- Complete, signed, and stamped tender document including amendments and deviation sheets, if any (to be uploaded online only).
- Declaration of agreed specifications on company letterhead, duly signed and stamped.
- Any other documents in support of technical eligibility.

All bidders are required to quote for all the items listed in the BoQ. Partial or item-wise quotations will be summarily rejected. Each bidder is allowed to submit only one quotation per package; multiple submissions from a single bidder will lead to disqualification.

3. Technical Documentation and Compliance

The bidder must furnish complete technical documentation for each quoted item. This includes detailed product specifications, installation manuals, operation and maintenance manuals. The bidder is also required to submit a layout/design proposal aligned with the lab setup requirements, highlighting compliance points against the tender specifications.

Original technical brochures or scanned versions of product catalogs should be submitted with the bid. Wherever available, URLs to the OEM's official product page should also be provided for cross-verification.

Each bidder must clearly mention the make, model, and complete technical specifications for the equipment being offered. A compliance sheet responding to each technical requirement outlined in the tender must be prepared and duly signed.

4. Eligibility and Qualification Criteria

All bidders must be OEMs or authorized partners/distributors with valid authorization for the products they are quoting. Authorization letters must be submitted on the OEM's official letterhead.

Bidders must demonstrate relevant experience by submitting a minimum of three Purchase Orders (executed within the last five years) for similar equipment supplied to academic, R&D, or industrial institutions. A list of at least five institutional clients (with contact information) must be provided as a reference.



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY

ADDING VALUE TO ENGINEERING

Approved by AICTE, New Delhi, Recognized by Govt. of Maharashtra,
Affiliated to Savitribai Phule Pune University (ID No. PU / PN / ENGG / 124 / 1998)

Accredited by NAAC with 'A' Grade



SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

Dr. PRADEEP B MANE
Principal

Ref. No.:

Date :

It is mandatory that the bidder or OEM has a registered support office in India to provide warranty and after-sales support. In the case of imported equipment, either the OEM or their authorized seller must submit a certificate confirming the presence of such a service support facility in India.

The OEM must also submit a declaration confirming the availability of spare parts for the quoted products for a minimum of one year and authorize the bidder to participate in the tender.

5. Financial Criteria

Each bidder must have an average annual turnover of ₹5 Crores or more over the last three financial years (FY 2022–23, 2023–24, 2024–25). The turnover must be supported by a CA certificate or audited financial statements.

Prices quoted must be inclusive of all taxes (GST, customs, etc.), transportation, packaging, insurance, unloading, installation, commissioning, and training charges. There shall be no extra claim under any circumstances after the finalization of the bid.

The quoted prices must be firm and fixed throughout the duration of the contract. No escalation in price will be allowed under any pretext.

6. Evaluation and Award of Contract

All bids will be evaluated on the basis of compliance with the technical specifications, completeness of submitted documentation, financial eligibility, and price competitiveness. The contract shall be awarded to the bidder whose offer is determined to be technically responsive and lowest in cost. The purchaser reserves the absolute right to reject any or all bids without assigning any reason. The final decision on selection will be at the sole discretion of the purchaser and shall be binding on all parties.

7. Warranty and After-Sales Service

All equipment must carry a minimum onsite warranty of at least **three years** from the date of successful installation and commissioning. During this warranty period, the bidder shall repair or replace any defective items at no additional cost to the purchaser. All associated transportation, testing, and labor costs shall be borne by the bidder.



AISSMS

INSTITUTE OF INFORMATION TECHNOLOGY

ADDING VALUE TO ENGINEERING

Approved by AICTE, New Delhi, Recognized by Govt. of Maharashtra,
Affiliated to Savitribai Phule Pune University (ID No. PU / PN / ENGG / 124 / 1998)

Accredited by NAAC with 'A' Grade



SHRI MALOJIRAJE CHHATRAPATI
Honorary Secretary

Dr. PRADEEP B MANE
Principal

Ref. No.:

Date :

In case of any service delay or failure to resolve issues during the warranty period, the purchaser reserves the right to invoke penalties or reject future business from the vendor.

8. Payment Terms

Payment shall be released only after the successful supply, installation, and commissioning of the equipment. Final inspection and acceptance will be carried out by the purchaser's technical committee.

No payment shall be made for equipment that is received in damaged condition, is non-functional, or fails to meet the required specifications. The bidder must submit all necessary documentation (delivery challans, installation report, warranty documents, training certificate, invoice, etc.) to process payment.

9. Other Conditions

No bidder shall be given preference based on category, class, or affiliation. The procurement may be extended to additional phases (e.g., Phase II) depending on availability of funds and institutional requirements.

Delayed delivery or installation may result in cancellation of order or imposition of penalties, as deemed fit by the purchaser. The scope of the supply and service must be entirely as per the BoQ and technical specifications. Bids with partial compliance or deviations shall not be entertained.

10. Submission Deadline and Contact Details

All quotations must be submitted by 9/08/2025 (before 5:00 pm) to the email ID principal@aisssmsioit.org or sent in hard copy to:

AISSMS Institute Of Information Technology

Kennedy Road, Near RTO, Pune 411001

Contact: Dr. Y. P. Patil (09421051726)

Email: Yogesh.patil@aisssmsioit.org